







#### **Fixture Number**

DP-93-24 9.5"H x 24" Dia. 36" Oah. 11.25"H x 30" Dia. 37" Oah. DP-93-30

DP-93-36 13"H x 36" Dia. 39" Oah.

## Finish

Standard Painted Finishes (PT)

Faux Antique Brass (FAB)

### Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

### DP-93-24

LED Options	Lumens	Wattage
B64 Uplight + Downlight	2545 up/1855 down (delivered)	64

# Non-LED Lamps

3N100: (3) 100 watt incandescent

### DP-93-30

LED Options	Lumens	Wattage
B95R Uplight + Downlight	5090 up/1855 down (delivered)	95

# Non-LED Lamps

6N60: (6) 60 watt incandescent

#### DP-93-36

LED Options	Lumens	Wattage
B145R Uplight + Downlight	8309 up/2782 down (delivered)	145

**LED Dimming** 

D0: 0-10v

#### Non-LED Lamps

6N100: (6) 100 watt incandescent

**LED Color Temp** 

27: 2700K

30: 3000K

35: 3500K

40: 4000K

D1: Triac (Leading Edge)\* D2: ELV (Trailing Edge)

**Voltage Options** 

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

**Diffuser Options** 

WH: White Acrylic

FX: Faux Alabaster Acrylic

Stem Options

Single Stem (SIN)

Traditional Chain (TCH)



Satellite Rods (QAD)