


1 Fixture Number

DP-93-24 9.5"H x 24" Dia. 36" Oah.
 DP-93-30 11.25"H x 30" Dia. 37" Oah.
 DP-93-36 13"H x 36" Dia. 39" Oah.

2 Finish

Standard Painted Finishes (PT)
 Faux Antique Brass (FAB)

3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DP-93-24

| LED Options | Lumens | Wattage |
|-------------------------|-------------------------------|---------|
| B64 Uplight + Downlight | 2545 up/1855 down (delivered) | 64 |

Non-LED Lamps

3N100: (3) 100 watt incandescent

DP-93-30

| LED Options | Lumens | Wattage |
|--------------------------|-------------------------------|---------|
| B95R Uplight + Downlight | 5090 up/1855 down (delivered) | 95 |

Non-LED Lamps

6N60: (6) 60 watt incandescent

DP-93-36

| LED Options | Lumens | Wattage |
|---------------------------|-------------------------------|---------|
| B145R Uplight + Downlight | 8309 up/2782 down (delivered) | 145 |

Non-LED Lamps

6N100: (6) 100 watt incandescent

4 LED Color Temp

27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic
 FX: Faux Alabaster Acrylic

8 Stem Options


| | | | | | | | |
|-----------|-----------------|----------|------------|----------|----------|----------|----------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| Fixture # | Finish (Finish) | Lamping | Color Temp | Dimming | Voltage | Diffuser | Stem |