



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of an acrylic bowl diffuser with a spun aluminum or brass finial pan and painted white canopy.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- UL and C-UL listed for dry or damp locations.

- 1 Fixture Number**
DC-330 9"H x 17.75" Dia.
DC-332 9.25"H x 25.75" Dia.

- 2 Finish**
 Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)
 Polished Brass (PB)

- 3 Lamping**
 All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DC-330

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

- Non-LED Lamps**
 3N60: (3) 60 watt incandescent
 2FQ26: (2) 26 watt compact fluorescent

DC-332

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

- Non-LED Lamps**
 3N60: (3) 60 watt incandescent
 4FQ26: (4) 26 watt compact fluorescent

- 4 LED Color Temp**
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K
- 5 LED Dimming**
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

- 6 Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**
 WH: Opal White Acrylic
 FX: Faux Alabaster Acrylic

- 8 Fixture Options**
 DM: Fluorescent Dimming
 *SP: 10kA surge protector (Recommended for D1 dimming option)

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Fixture Option