



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of an acrylic bowl diffuser, extruded aluminum or brass rectangular support arm and a fabricated aluminum or brass wall plate.
- **MOUNTING:** Fixture mounts to standard octagonal junction box. Additional structural blocking required to support fixture.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

DS-211 17.75"W x 9.5"H x 19.5" Ext.
DS-213 25.75"W x 10.5"H x 27.5" Ext.

2 Finish

Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)
 Polished Brass (PB)

3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DS-211

LED Options	Lumens	Wattage
S32	3440 (initial)	32

Non-LED Lamps

3N100: (3) 100 watt incandescent

DS-213

LED Options	Lumens	Wattage
S65	6995 (initial)	65

Non-LED Lamps

4N100: (4) 100 watt incandescent

4 LED Color Temp

27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic
 FX: Faux Alabaster Acrylic

1

Fixture #

2

Finish
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser