



**1 Fixture Number**

- DP-280** 6"H x 17.75" Dia. 32" Oah.
- DP-282** 7"H x 25.75" Dia. 45" Oah.
- DP-286** 9.5"H x 33.5" Dia. 59" Oah.

**2 Finish**

- Brushed Solid Aluminum (BA)
- Standard Painted Finishes (PT)
- Polished Brass (PB)

**3 Lamping**

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**DP-280**

LED Options	Lumens	Wattage
B32 Uplight + Downlight	1097 up/1097 down (delivered)	32

**Non-LED Lamps**

3N100: (3) 100 watt incandescent

**DP-282**

LED Options	Lumens	Wattage
B64 Uplight + Downlight	2545 up/1855 down (delivered)	64

**Non-LED Lamps**

4N100: (4) 100 watt incandescent

**DP-286**

LED Options	Lumens	Wattage
B145R Uplight + Downlight	8309 up/2782 down (delivered)	145

**Non-LED Lamps**

6N100: (6) 100 watt incandescent

**4 LED Color Temp**

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

**5 LED Dimming**

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)

**6 Voltage Options**

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**

- WH: White Acrylic
- FX: Faux Alabaster Acrylic

**8 Stem Options**

