



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of solid cast aluminum trim panels with fabricated steel corner trim posts.
- MOUNTING: Fixture mounts to a standard octagonal junction box. LPI-345-16 must be attached to structure using a ceiling fan rated electrical box.
- OVERALL HEIGHT: Standard OAH includes fixture height plus 3' chain to spreader and 6' main chain to ceiling.
- CIRCUITS: Dual-level circuiting for interior lamps/downlight standard.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

- LPI-345-11** 25"H x 11.75" Dia. 133" Oah.
- LPI-345-13** 31"H x 13.25" Dia. 139" Oah.
- LPI-345-16** 37.5"H x 16.5" Dia. 145" Oah.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LPI-345-11

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P50 Body (14w) + Downlight (36w)	5881 (initial)	50

Non-LED Lamps

3N60 / 1R300: (3) 60 watt incandescent & (1) 300 watt R40 med. base

LPI-345-13

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P63 Body (27w) + Downlight (36w)	5471 (delivered)	63

Non-LED Lamps

6N60 / 1R500: (6) 60 watt incandescent & (1) 500 watt R40 med. base

LPI-345-16

LED Options	Lumens	Wattage
P40 Body only w/bottom lens (40w)	3796 (delivered)	40
P136 Body (40w) + Downlight (96w)	16129 (initial)	136
U44 Optional Uplight (44w)	4038 (delivered)	44

Non-LED Lamps

6N60 / 1R500: (6) 60 watt incandescent & (1) 500 watt R40 med. base

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)*
- D2: ELV (Trailing Edge)

6 Downlight Optics Options

- B60: 60-deg. beam reflector
- B90: 90-deg. beam reflector
- CON: Concentric Ring Louver (approx. 50-deg. beam)

7 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

- WH: Opal White Acrylic
- IV: Ivory acrylic
- FX: Faux Alabaster Acrylic

1

Fixture #

2

Finish
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Downlight Opti

7

Voltage

8

Diffuser