



Notes

- LED option replaces bottom louver with white acrylic diffuser.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of solid cast aluminum trim panels, chain spreader with fabricated steel corner trim posts.
- MOUNTING: Structural support is required for this heavy fixture. Requires 2 x 4 blocking or 1/2" IP stud extending 1/2" below finished ceiling through center of octagonal junction box.
- CIRCUITS: Wired for two or three circuits with separate neutrals.
- OVERALL HEIGHT: Standard OAH includes fixture height plus 6' chain to spreader and 6' main chain to ceiling.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

- CPI-431-38** 26"H x 38" Dia. 170" Oah.
CPI-431-38A 26"H x 38" Dia. 170" Oah.
CPI-431-48 33.25"H x 48" Dia. 177" Oah.
CPI-431-48A 33.25"H x 48" Dia. 177" Oah.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency. Body, uplights, and downlights separately circuited.

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P245 Body + Downlights	22344 (initial)	245

Non-LED Lamps

6R300 / 1R500 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (6) 100 watt incandescent

CPI-431-38A

Includes (7) 28w LED downlight and (3) 28w uplight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P329 Body + Downlights + Uplights	31920 (initial)	329

Non-LED Lamps

6R300 / 1R500 / 3R300 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (3) 300 watt R40 med. base & (6) 100 watt incandescent

CPI-431-48

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P259 Body + Downlights	31632 (initial)	259

Non-LED Lamps

6R300 / 1R500 / 6R300 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (6) 300 watt R40 med. base & (6) 100 watt incandescent

CPI-431-48A

Includes (9) 28w LED downlight and (4) 28w uplight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P427 Body + Downlights + Uplights	50784 (initial)	427

Non-LED Lamps

6R300 / 1R500 / 6R300 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (6) 300 watt R40 med. base & (6) 100 watt incandescent

4 LED Color Temp

- 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

- D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Downlight Optics Options

- B60: 60-deg. beam reflector
 B90: 90-deg. beam reflector
 CON: Concentric Ring Louver (approx. 50-deg. beam)

7 Voltage Options

- 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

- WH: Opal White Acrylic
 IV: Ivory acrylic
 FX: Faux Alabaster Acrylic

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser