




Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Solid aluminum plate top and bottom end caps, extruded aluminum corner posts and laser-cut aluminum accent panel.
- MOUNTING: Fixture mounts to a 2 x 4 switch box.
- ETL listed to UL standards for wet locations.
- Fluorescent ballasts rated to - 22-degree F

1 Fixture Number

DE-254 4"W x 21.3"H x 4" Ext.

DE-256 4"W x 25.2"H x 4" Ext.

DE-258 4"W x 31.2"H x 4" Ext.

2 Finish

Trim

Standard Painted Finishes (PT)

Panel

Standard Painted Finishes (PT)

Raw Copper (CU)

3 Lamping

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DE-254

LED Options	Lumens	Wattage
E11	818 (initial)	11

DE-256

LED Options	Lumens	Wattage
E17	1226 (initial)	17

DE-258

LED Options	Lumens	Wattage
E23	1636 (initial)	23

4 LED Color Temp

27: 2700K

30: 3000K

35: 3500K

40: 4000K

5 LED Dimming

D0: 0-10v

6 Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic

FX: Faux Alabaster Acrylic

8 Panel Options



E1



E2



E3



E4



E5



E6

1	2	2	3	4	5	6	7	8
Fixture #	Trim (Finish)	Panel (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Panel