



**Notes**

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Solid aluminum plate top and bottom end caps, extruded aluminum corner posts and laser-cut aluminum accent panel.
- MOUNTING: Fixture mounts to a 2 x 4 switch box.
- ETL listed to UL standards for wet locations.
- Fluorescent ballasts rated to - 22-degree F

**1 Fixture Number**

- DE-254 4"W x 21.3"H x 4" Ext.
- DE-256 4"W x 25.2"H x 4" Ext.
- DE-258 4"W x 31.2"H x 4" Ext.

**2 Finish**

- Trim**  
Standard Painted Finishes (PT)
- Panel**  
Standard Painted Finishes (PT)  
Raw Copper (CU)

**3 Lamping**

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**DE-254**

LED Options	Lumens	Wattage
E11	818 (initial)	11

**DE-256**

LED Options	Lumens	Wattage
E17	1226 (initial)	17

**DE-258**

LED Options	Lumens	Wattage
E23	1636 (initial)	23

**4 LED Color Temp**

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

**5 LED Dimming**

D0: 0-10v

**6 Voltage Options**

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**

- WH: Opal White Acrylic
- FX: Faux Alabaster Acrylic

**8 Panel Options**

