


**1 Fixture Number**

**DP-46-12** 12"H x 12" Dia. 52" Oah.  
**DP-46-14** 14"H x 14" Dia. 54" Oah.  
**DP-46-16** 16"H x 16" Dia. 56" Oah.  
**DP-46-18** 18"H x 18" Dia. 58" Oah.

**2 Finish**

Standard Painted Finishes (PT)

**3 Lamping**

LED option includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**DP-46-12**

LED Options	Lumens	Wattage
P20 Uplight + Downlight	2383 (delivered)	20

**Non-LED Lamps**

1N60: (1) 60 watt incandescent

**DP-46-14**

LED Options	Lumens	Wattage
P20 Uplight + Downlight	2383 (delivered)	20

**Non-LED Lamps**

1N60: (1) 60 watt incandescent

**DP-46-16**

LED Options	Lumens	Wattage
P20 Uplight + Downlight	2383 (delivered)	20

**Non-LED Lamps**

1N60: (1) 60 watt incandescent

**DP-46-18**

LED Options	Lumens	Wattage
P20 Uplight + Downlight	2383 (delivered)	20

**Non-LED Lamps**

1N60: (1) 60 watt incandescent

**4 LED Color Temp**

27: 2700K

30: 3000K

35: 3500K

40: 4000K

**5 LED Dimming**

D0: 0-10v

D1: Triac (Leading Edge)\*

D2: ELV (Trailing Edge)

**6 Voltage Options**

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**

WHG: Opal White Glass

**8 Fixture Options**

REM: Remote driver box

DKC: Disk ceiling driver canopy

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Fixture Option