



- 1 Fixture Number**  
**DP-46-10** 10"H x 10" Dia. 52" Oah.  
**DP-46-12** 12"H x 12" Dia. 52" Oah.  
**DP-46-14** 14"H x 14" Dia. 54" Oah.  
**DP-46-16** 16"H x 16" Dia. 56" Oah.

- 2 Finish**  
 Standard Painted Finishes (PT)

- 3 Lamping**  
 LED option includes canopy-mounted 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**DP-46-10**

LED Options	Lumens	Wattage
P20 Uplight + Downlight	2383 (delivered)	20

**Non-LED Lamps**  
 1N60: (1) 60 watt incandescent

**DP-46-12**

LED Options	Lumens	Wattage
P39 Celeste	4000 delivered	39

**Non-LED Lamps**  
 1N60: (1) 60 watt incandescent

**DP-46-14**

LED Options	Lumens	Wattage
P39 Celeste	4000 delivered	39

**Non-LED Lamps**  
 1N60: (1) 60 watt incandescent

**DP-46-16**

LED Options	Lumens	Wattage
P39 Celeste	4000 delivered	39

**Non-LED Lamps**  
 1N60: (1) 60 watt incandescent

- 4 LED Color Temp**  
 27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

- 5 LED Dimming**  
 D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

- 6 Voltage Options**  
 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**  
 WHG: Opal White Glass

- 8 Panel Options**
- 
- CL0 CL1 CL2 CL3 CL4 CL5

- 9 Fixture Options**  
 REM: Remote driver box  
 DKC: Disk ceiling driver canopy