



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of solid cast aluminum trim panels with fabricated steel corner trim posts.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box. LPI-305-16 and -18 must be attached to structure using a ceiling fan rated electrical box.
- **CIRCUITS:** Wired for one, two or three circuits.
- **OVERALL HEIGHT:** Standard OAH includes fixture height plus 6' main chain to ceiling.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

- LPI-305-08** 26"H x 8.25" Dia. 98" Oah.
LPI-305-11 29"H x 11.5" Dia. 101" Oah.
LPI-305-13 39"H x 13.5" Dia. 111" Oah.
LPI-305-16 45.75"H x 16.5" Dia. 118" Oah.
LPI-305-18 56.5"H x 18.5" Dia. 128" Oah.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LPI-305-08

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27

Non-LED Lamps

1N100: (1) 100 watt incandescent

LPI-305-11

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P63 Body (27w) + Downlight (36w)	5471 (delivered)	63

Non-LED Lamps

3N60 / 1R300: (3) 60 watt incandescent & (1) 300 watt R40 med. base

LPI-305-13

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P63 Body (27w) + Downlight (36w)	5471 (delivered)	63

Non-LED Lamps

3N60 / 1R500: (3) 60 watt incandescent & (1) 500 watt R40 med. base

LPI-305-16

LED Options	Lumens	Wattage
P40 Body only w/bottom lens (40w)	3796 (delivered)	40
P136 Body (40w) + Downlight (96w)	16129 (initial)	136
U18 Optional Uplight (18w)	1613 (delivered)	18

Non-LED Lamps

3N60 / 3R300 / 1R500: (3) 60 watt incandescent & (3) 300 watt R40 med. base & (1) 500 watt R40 med. base

LPI-305-18

LED Options	Lumens	Wattage
P54 Body only w/bottom lens (54w)	5555 (delivered)	54
P109 Body (54w) + Downlight (55w)	11760 (delivered)	109
P150 Body (54w) + Downlight (96w)	14818 (delivered)	150
U44 Optional Uplight (44w)	4038 (delivered)	44

Non-LED Lamps

3N60 / 3R300 / 1R500: (3) 60 watt incandescent & (3) 300 watt R40 med. base & (1) 500 watt R40 med. base

4 LED Color Temp

- 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

- D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Downlight Optics Options

- B60: 60-deg. beam reflector
 B90: 90-deg. beam reflector
 CON: Concentric Ring Louver (approx. 50-deg. beam)

7 Voltage Options

- 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

- WH: White Acrylic
 IV: Ivory acrylic
 FX: Faux Alabaster Acrylic

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser