



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Solid cast aluminum trim bands, corner posts and support bars. White acrylic diffuser.
- MOUNTING: Fixture mounts to a standard octagonal junction box. LPI-304-17 must be attached to structure using a ceiling fan rated electrical box.
- CIRCUITS: Wired for one, two or three circuits.
- OVERALL HEIGHT: Standard OAH includes fixture height plus 6' main chain to ceiling.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

- LPI-304-09** 25.75"H x 9.5" Dia. 98" Oah.
- LPI-304-11** 34.75"H x 11.5" Dia. 107" Oah.
- LPI-304-13** 42.5"H x 13.5" Dia. 115" Oah.
- LPI-304-17** 55.5"H x 17.5" Dia. 128" Oah.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LPI-304-09

| LED Options | Lumens | Wattage |
|-----------------------------------|------------------|---------|
| P27 Body only w/bottom lens (27W) | 2730 (delivered) | 27 |

Non-LED Lamps

1N100: (1) 100 watt incandescent

LPI-304-11

| LED Options | Lumens | Wattage |
|-----------------------------------|------------------|---------|
| P27 Body only w/bottom lens (27W) | 2730 (delivered) | 27 |
| P63 Body (27w) + Downlight (36w) | 5471 (delivered) | 63 |

Non-LED Lamps

3N60 / 1R300: (3) 60 watt incandescent & (1) 300 watt R40 med. base

LPI-304-13

| LED Options | Lumens | Wattage |
|-----------------------------------|------------------|---------|
| P40 Body only w/bottom lens (40w) | 3796 (delivered) | 40 |
| P88 Body (40w) + Downlight (48w) | 8128 (delivered) | 88 |

Non-LED Lamps

3N60 / 3R300 / 1R500: (3) 60 watt incandescent & (3) 300 watt R40 med. base & (1) 500 watt R40 med. base

LPI-304-17

| LED Options | Lumens | Wattage |
|-----------------------------------|-------------------|---------|
| P54 Body only w/bottom lens (54w) | 5555 (delivered) | 54 |
| P109 Body (54w) + Downlight (55w) | 11760 (delivered) | 109 |
| P150 Body (54w) + Downlight (96w) | 14818 (delivered) | 150 |
| U44 Optional Uplight (44w) | 4038 (delivered) | 44 |

Non-LED Lamps

3N60 / 3R300 / 1R500: (3) 60 watt incandescent & (3) 300 watt R40 med. base & (1) 500 watt R40 med. base

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)*
- D2: ELV (Trailing Edge)

6 Downlight Optics Options

- B60: 60-deg. beam reflector
- B90: 90-deg. beam reflector
- CON: Concentric Ring Louver (approx. 50-deg. beam)

7 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

- WH: Opal White Acrylic

| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|-----------|-----------------|---------|------------|---------|----------------|---------|----------|
| Fixture # | Finish (Finish) | Lamping | Color Temp | Dimming | Downlight Opti | Voltage | Diffuser |