



**1 Fixture Number**

- LPI-305-08** 26"H x 8.25" Dia. 98" Oah.
- LPI-305-11** 29"H x 11.5" Dia. 101" Oah.
- LPI-305-13** 39"H x 13.5" Dia. 111" Oah.
- LPI-305-16** 45.75"H x 16.5" Dia. 118" Oah.
- LPI-305-18** 56.5"H x 18.5" Dia. 128" Oah.

**2 Finish**

Standard Painted Finishes (PT)

**3 Lamping**

LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**LPI-305-08**

| LED Options                       | Lumens           | Wattage |
|-----------------------------------|------------------|---------|
| P27 Body only w/bottom lens (27W) | 2730 (delivered) | 27      |

**Non-LED Lamps**

1N100: (1) 100 watt incandescent

**LPI-305-11**

| LED Options                       | Lumens           | Wattage |
|-----------------------------------|------------------|---------|
| P27 Body only w/bottom lens (27W) | 2730 (delivered) | 27      |
| P63 Body (27w) + Downlight (36w)  | 5471 (delivered) | 63      |

**Non-LED Lamps**

3N60 / 1R300: (3) 60 watt incandescent & (1) 300 watt R40 med. base

**LPI-305-13**

| LED Options                       | Lumens           | Wattage |
|-----------------------------------|------------------|---------|
| P27 Body only w/bottom lens (27W) | 2730 (delivered) | 27      |
| P63 Body (27w) + Downlight (36w)  | 5471 (delivered) | 63      |

**Non-LED Lamps**

3N60 / 1R500: (3) 60 watt incandescent & (1) 500 watt R40 med. base

**LPI-305-16**

| LED Options                       | Lumens           | Wattage |
|-----------------------------------|------------------|---------|
| P40 Body only w/bottom lens (40w) | 3796 (delivered) | 40      |
| P136 Body (40w) + Downlight (96w) | 16129 (initial)  | 136     |
| U18 Optional Uplight (18w)        | 1613 (delivered) | 18      |

**Non-LED Lamps**

3N60 / 3R300 / 1R500: (3) 60 watt incandescent & (3) 300 watt R40 med. base & (1) 500 watt R40 med. base

**LPI-305-18**

| LED Options                       | Lumens            | Wattage |
|-----------------------------------|-------------------|---------|
| P54 Body only w/bottom lens (54w) | 5555 (delivered)  | 54      |
| P109 Body (54w) + Downlight (55w) | 11760 (delivered) | 109     |
| P150 Body (54w) + Downlight (96w) | 14818 (delivered) | 150     |
| U44 Optional Uplight (44w)        | 4038 (delivered)  | 44      |

**Non-LED Lamps**

3N60 / 3R300 / 1R500: (3) 60 watt incandescent & (3) 300 watt R40 med. base & (1) 500 watt R40 med. base

**4 LED Color Temp**

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

**5 LED Dimming**

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)

**6 Downlight Optics Options**

- B60: 60-deg. beam reflector
- B90: 90-deg. beam reflector
- CON: Concentric Ring Louver (approx. 50-deg. beam)

**7 Voltage Options**

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

**8 Diffuser Options**

- WH: White Acrylic
- IV: Ivory acrylic
- FX: Faux Alabaster Acrylic

| 1         | 2               | 3       | 4          | 5       | 6              | 7       | 8        |
|-----------|-----------------|---------|------------|---------|----------------|---------|----------|
| Fixture # | Finish (Finish) | Lamping | Color Temp | Dimming | Downlight Opti | Voltage | Diffuser |