



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of solid cast aluminum trim panels with fabricated steel corner trim posts.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number
LBI-305 8.25"W x 16"H x 5" Ext.

2 Finish
Standard Painted Finishes (PT)

3 Lamping
LED option includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.
LBI-305

| LED Options | Lumens | Wattage |
|-------------|-----------------|---------|
| S7 | 612 (delivered) | 7 |

Non-LED Lamps
1N60: (1) 60 watt incandescent

4 LED Color Temp
27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming
D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Voltage Options
120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options
WH: White Acrylic
IV: Ivory acrylic
FX: Faux Alabaster Acrylic

| | | | | | | |
|-----------|-----------------|---------|------------|---------|---------|----------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| Fixture # | Finish (Finish) | Lamping | Color Temp | Dimming | Voltage | Diffuser |