



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of white thermoformed acrylic with laser-cut accent panels and painted canopy.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- UL and C-UL listed for dry or damp locations.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number
CC-250 16.25"W x 6.5"H x 16.25"L

2 Finish
Trim
 Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)
 Faux Antique Brass (FAB)

3 Lamping
 All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

CC-250

| LED Options | Lumens | Wattage |
|-------------|------------------|---------|
| C26 | 2178 (delivered) | 26 |
| C38 | 3118 (delivered) | 38 |

Non-LED Lamps
 3N60: (3) 60 watt incandescent
 4F18: (4) 18 watt compact fluorescent

4 LED Color Temp
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Voltage Options
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options
 WH: Opal White Acrylic

8 Fixture Options
 FU: Fusing
 EMI: Integral Emergency Battery (Fluor.)

