



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of an adjustable fabricated aluminum reflector housing and fabricated aluminum wall mounting plate.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**
HO-740 17.5"W x 7.5"H x 10.75" Ext.
HO-742 26"W x 7.5"H x 10.75" Ext.
HO-744 30"W x 7.5"H x 10.75" Ext.

- 2 Finish**
 Standard Painted Finishes (PT)

- 3 Lamping**
 LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

HO-740

LED Options	Lumens	Wattage
S16	995 (delivered)	16

HO-742

LED Options	Lumens	Wattage
S32	3440 (initial)	32

HO-744

LED Options	Lumens	Wattage
S64	6880 (initial)	64

- 4 LED Color Temp**
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

- 5 LED Dimming**
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

- 6 Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

