



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of an adjustable fabricated aluminum reflector housing and fabricated aluminum wall mounting plate.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

HO-780 17.5"W x 6"H x 15.25" Ext.
HO-782 26"W x 6"H x 15.25" Ext.
HO-784 30"W x 6"H x 15.25" Ext.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

HO-780

| LED Options | Lumens | Wattage |
|-------------|-----------------|---------|
| S16 | 995 (delivered) | 16 |

HO-782

| LED Options | Lumens | Wattage |
|-------------|----------------|---------|
| S32 | 3440 (initial) | 32 |

HO-784

| LED Options | Lumens | Wattage |
|-------------|----------------|---------|
| S64 | 6880 (initial) | 64 |

4 LED Color Temp

27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

1

Fixture #

2

Finish
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage