



**1 Fixture Number**

- HO-780** 17.5"W x 6"H x 15.25" Ext.
- HO-782** 26"W x 6"H x 15.25" Ext.
- HO-784** 30"W x 6"H x 15.25" Ext.

**2 Finish**

Standard Painted Finishes (PT)

**3 Lamping**

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**HO-780**

LED Options	Lumens	Wattage
S16	995 (delivered)	16

**HO-782**

LED Options	Lumens	Wattage
S32	3440 (initial)	32

**HO-784**

LED Options	Lumens	Wattage
S64	6880 (initial)	64

**4 LED Color Temp**

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

**5 LED Dimming**

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)

**6 Voltage Options**

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

1

Fixture #

2

Finish  
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage