



## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of a white thermoformed acrylic diffuser with a painted white canopy.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

**1 Fixture Number**  
**CC-208** 6.5"H x 16" Dia.

**2 Lamping**  
 All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

**Non-LED Lamps**  
 3N60: (3) 60 watt incandescent

**3 LED Color Temp**  
 27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

**4 LED Dimming**  
 D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

**5 Voltage Options**  
 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

**6 Diffuser Options**  
 WH: Opal White Acrylic

