



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of a white thermoformed acrylic diffuser with a painted white canopy.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

CC-208 6.5"H x 16" Dia.

2 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

CC-208

| LED Options | Lumens | Wattage |
|-------------|------------------|---------|
| C26 | 2178 (delivered) | 26 |
| C38 | 3118 (delivered) | 38 |

Non-LED Lamps

3N60: (3) 60 watt incandescent

3 LED Color Temp

27: 2700K

30: 3000K

35: 3500K

40: 4000K

4 LED Dimming

D0: 0-10v

D1: Triac (Leading Edge)*

D2: ELV (Trailing Edge)

5 Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

6 Diffuser Options

WH: White Acrylic

1

Fixture #

2

Lamping

3

Color Temp

4

Dimming

5

Voltage

6

Diffuser