



## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of a white thermoformed acrylic diffuser with a painted white canopy.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

**CC-208** 6.5"H x 16" Dia.

### 2 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### CC-208

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

#### Non-LED Lamps

3N60: (3) 60 watt incandescent

### 3 LED Color Temp

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

### 4 LED Dimming

D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

### 5 Voltage Options

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

### 6 Diffuser Options

WH: Opal White Acrylic

1

Fixture #

2

Lamping

3

Color Temp

4

Dimming

5

Voltage

6

Diffuser