



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of a white thermoformed acrylic diffuser with a painted white canopy.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

**1 Fixture Number**  
**CC-208** 6.5"H x 16" Dia.

**2 Lamping**  
All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

### CC-208

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

### Non-LED Lamps

3N60: (3) 60 watt incandescent

**3 LED Color Temp**

27: 2700K

30: 3000K

35: 3500K

40: 4000K

**4 LED Dimming**

D0: 0-10v

D1: Triac (Leading Edge)\*

D2: ELV (Trailing Edge)

**5 Voltage Options**

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

**6 Diffuser Options**

WH: White Acrylic

1

Fixture #

2

Lamping

3

Color Temp

4

Dimming

5

Voltage

6

Diffuser