
Hanning Lighting





Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of a white thermoformed acrylic diffuser with spun aluminum downlight bezel assembly.
- MOUNTING: Fixture supplied with a painted canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- CIRCUITS: Dual-level circuiting for interior lamps/downlight standard.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

Height Pendant (Bowl)

LP-218 LP-220	12"H x 22" Dia. 12.5"H x 26" Dia							
LP-222								
2 Finish								
	olid Aluminum (BA) Painted Finishes (PT))						
0-10v, Triac,	and ELV controls. C	120-277v 1-100% dimming driver compat Over-current and short-circuit protected. All L e listed includes driver efficiency.						
LP-218								
LED Options		Lumens	Wattage					
B49 Uplight -		6009 (initial)	49					
		incandescent & (1) 120 watt PAR 38 quartz	halogen					
LP-220 LED Options	e	Lumens	Wattage					
B66 Uplight -		8080 (initial)	66					
Non-LED L	amps	ncandescent & (1) 500 watt R40 med. base						
LP-222	1000. (0) 100 watt ii	icandescent & (1) 500 watt 140 med. base						
LED Options	S	Lumens	Wattage					
B95 Uplight -		5160 up/4984 down (delivered)	95					
ECR: Black 7 Voltage Optio 120: 120 volt	centric Ring Louver (< Egg Crate Louver (ins t t (Not available with i ons	D1: Triac (Leading Edge)* D2: ELV (Trailing Edge) (approx. 50-deg. beam) (approx. 40-deg. beam)						

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser

©2018 Manning Lighting Inc. Sheboygan, WI 53083 Phone: 920-458-2184 Web: manningltg.com Email: info@manningltg.com Design modification rights reserved. Made in USA.