







Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of a white thermoformed acrylic diffuser with spun aluminum downlight bezel assembly.
- MOUNTING: Fixture supplied with a painted canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- CIRCUITS: Dual-level circuiting for interior lamps/downlight standard.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

Fixture Number

LP-218 12"H x 22" Dia. 38" Oah. LP-220 12.5"H x 26" Dia. 51" Oah. LP-222 14.75"H x 34" Dia. 65" Oah.

Finish

Brushed Solid Aluminum (BA) Standard Painted Finishes (PT)

Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LP-218

			
LED Options	Lumens	Wattage	
B49 Uplight + Downlight	6009 (initial)	49	

Non-LED Lamps

3N100 / 1QP120: (3) 100 watt incandescent & (1) 120 watt PAR 38 quartz halogen

LP-220

LED Options	Lumens	Wattage
B66 Uplight + Downlight	8080 (initial)	66

Non-LED Lamps

6N100 / 1R500: (6) 100 watt incandescent & (1) 500 watt R40 med. base

LP-222

LED Options	Lumens	Wattage
B95 Uplight + Downlight	5160 up/4984 down (delivered)	95

Non-LED Lamps

6N100 / 1R500: (6) 100 watt incandescent & (1) 500 watt R40 med. base

LED Color Temp

27: 2700K

LED Dimming D0: 0-10v

30: 3000K 35: 3500K 40: 4000K

D1: Triac (Leading Edge)* D2: ELV (Trailing Edge)

Downlight Optics Options

CON: Concentric Ring Louver (approx. 50-deg. beam) ECR: Black Egg Crate Louver (approx. 40-deg. beam)

Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

Diffuser Options

WH: Opal White Acrylic