



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of a white thermoformed acrylic diffuser with spun aluminum downlight bezel assembly.
- **MOUNTING:** Fixture supplied with a painted canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- **CIRCUITS:** Dual-level circuiting for interior lamps/downlight standard.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

- LP-219** 11.25"H x 17.25" Dia. 38" Oah.
LP-221 12.5"H x 24" Dia. 51" Oah.
LP-223 12.5"H x 30" Dia. 65" Oah.

2 Finish

- Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)

3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LP-219

| LED Options | Lumens | Wattage |
|-------------------------|----------------|---------|
| B49 Uplight + Downlight | 6009 (initial) | 49 |

Non-LED Lamps

3N100 / 1QP120: (3) 100 watt incandescent & (1) 120 watt PAR 38 quartz halogen

LP-221

| LED Options | Lumens | Wattage |
|-------------------------|----------------|---------|
| B66 Uplight + Downlight | 8080 (initial) | 66 |

Non-LED Lamps

6N100 / 1R500: (6) 100 watt incandescent & (1) 500 watt R40 med. base

LP-223

| LED Options | Lumens | Wattage |
|-------------------------|-------------------------------|---------|
| B95 Uplight + Downlight | 5160 up/4984 down (delivered) | 95 |

Non-LED Lamps

6N100 / 1R500: (6) 100 watt incandescent & (1) 500 watt R40 med. base

4 LED Color Temp

- 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

- D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Downlight Optics Options

- CON: Concentric Ring Louver (approx. 50-deg. beam)
 ECR: Black Egg Crate Louver (approx. 40-deg. beam)

7 Voltage Options

- 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

- WH: White Acrylic

| | | | | | | | |
|-----------|-----------------|---------|------------|---------|----------------|---------|----------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| Fixture # | Finish (Finish) | Lamping | Color Temp | Dimming | Downlight Opti | Voltage | Diffuser |