



### Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of a white thermoformed acrylic diffuser with spun aluminum downlight bezel assembly.
- **MOUNTING:** Fixture supplied with a painted canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- **CIRCUITS:** Dual-level circuiting for interior lamps/downlight standard.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

#### 1 Fixture Number

- LP-219** 11.25"H x 17.25" Dia. 38" Oah.  
**LP-221** 12.5"H x 24" Dia. 51" Oah.  
**LP-223** 12.5"H x 30" Dia. 65" Oah.

#### 2 Finish

- Brushed Solid Aluminum (BA)  
 Standard Painted Finishes (PT)

#### 3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

##### LP-219

LED Options	Lumens	Wattage
B49 Uplight + Downlight	6009 (initial)	49

##### Non-LED Lamps

3N100 / 1QP120: (3) 100 watt incandescent & (1) 120 watt PAR 38 quartz halogen

##### LP-221

LED Options	Lumens	Wattage
B66 Uplight + Downlight	8080 (initial)	66

##### Non-LED Lamps

6N100 / 1R500: (6) 100 watt incandescent & (1) 500 watt R40 med. base

##### LP-223

LED Options	Lumens	Wattage
B95 Uplight + Downlight	5160 up/4984 down (delivered)	95

##### Non-LED Lamps

6N100 / 1R500: (6) 100 watt incandescent & (1) 500 watt R40 med. base

#### 4 LED Color Temp

- 27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

#### 5 LED Dimming

- D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

#### 6 Downlight Optics Options

- CON: Concentric Ring Louver (approx. 50-deg. beam)  
 ECR: Black Egg Crate Louver (approx. 40-deg. beam)

#### 7 Voltage Options

- 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

#### 8 Diffuser Options

- WH: Opal White Acrylic

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser