



## Notes

- FINISH: PRIMARY FINISH = Corner extrusions, top and bottom plates. SECONDARY FINISH = Accent panels. Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Heavy gauge solid aluminum top and bottom frames with custom extruded aluminum corners. The side trim panels can be ordered with complementary color or finish.
- MOUNTING: Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**  
**CC-380** 18"W x 7.5"H x 18"L  
**CC-382** 24"W x 9"H x 24"L

- 2 Finish**
- |                                |                                |
|--------------------------------|--------------------------------|
| <b>Primary Finish</b>          | <b>Secondary Finish</b>        |
| Brushed Solid Aluminum (BA)    | Brushed Solid Aluminum (BA)    |
| Standard Painted Finishes (PT) | Standard Painted Finishes (PT) |

- 3 Lamping**  
 All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**CC-380**

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

- Non-LED Lamps**  
 3N60: (3) 60 watt incandescent  
 4F18: (4) 18 watt compact fluorescent

**CC-382**

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

- Non-LED Lamps**  
 3N60: (3) 60 watt incandescent  
 4F27: (4) 27 watt compact fluorescent

- 4 LED Color Temp**  
 27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K
- 5 LED Dimming**  
 D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

- 6 Voltage Options**  
 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**  
 WH: Opal White Acrylic  
 CD: Ambia configured diffuser (specify option)

- 8 Fixture Options**  
 EMI: Integral Emergency Battery (Fluor.)

1	2	2	3	4	5	6	7	8
Fixture #	Primary Finish (Finish)	Secondary Fini (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Fixture Option