



## Notes

- UL and C-UL listed for dry or damp locations.
- White bottom acrylic lens standard.
- OAH is standard unless specified.
- FINISH: PRIMARY FINISH = Canopy, corner extrusions, top and bottom plates. SECONDARY FINISH = Accent panels. Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Heavy gauge solid aluminum top and bottom frames with custom extruded aluminum corners. The side trim panels can be ordered with complementary color or finish. The fabricated aluminum wire body is coated with a reflective white enamel finish.
- MOUNTING: Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.

- Fixture Number**  
**DP-380** 18"W x 5.75"H x 18"L 32" Oah.  
**DP-382** 24"W x 6.75"H x 24"L 33" Oah.
- Finish**  

<b>Primary Finish</b>	<b>Secondary Finish</b>
Brushed Solid Aluminum (BA)	Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)	Standard Painted Finishes (PT)
- Lamping**  
 All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.  
**DP-380**

LED Options	Lumens	Wattage
B32 Uplight + Downlight	1097 up/1097 down (delivered)	32

**Non-LED Lamps**  
 3N60: (3) 60 watt incandescent  
 4F18: (4) 18 watt compact fluorescent

**DP-382**

LED Options	Lumens	Wattage
B65 Uplight + Downlight	2545 up/2630 down (delivered)	65

**Non-LED Lamps**  
 3N60: (3) 60 watt incandescent  
 4F39: (4) 39 watt compact fluorescent
- LED Color Temp**  
 27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K
- LED Dimming**  
 D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)
- Voltage Options**  
 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)
- Diffuser Options**  
 WH: Opal White Acrylic  
 CD: Ambia configured diffuser
- Fixture Options**  
 FU: Fusing  
 \*SP: 10kA surge protector (Recommended for D1 dimming option)

1	2	2	3	4	5	6	7	8
Fixture #	Primary Finish (Finish)	Secondary Fini (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Fixture Option