



- 1 Fixture Number**
CC-380 18"W x 7.5"H x 18"L
CC-382 24"W x 9"H x 24"L

- 2 Finish**
- | | |
|--------------------------------|--------------------------------|
| Primary Finish | Secondary Finish |
| Brushed Solid Aluminum (BA) | Brushed Solid Aluminum (BA) |
| Standard Painted Finishes (PT) | Standard Painted Finishes (PT) |

- 3 Lamping**
 All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

CC-380

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

Non-LED Lamps
 3N60: (3) 60 watt incandescent

CC-382

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

Non-LED Lamps
 3N60: (3) 60 watt incandescent

- | | |
|-------------------------|---------------------------|
| 4 LED Color Temp | 5 LED Dimming |
| 27: 2700K | D0: 0-10v |
| 30: 3000K | D1: Triac (Leading Edge)* |
| 35: 3500K | D2: ELV (Trailing Edge) |
| 40: 4000K | |

- 6 Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**
 WH: White Acrylic
 CD: Ambia configured diffuser (specify option)

1	2	2	3	4	5	6	7
Fixture #	Primary Finish (Finish)	Secondary Fini (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser