



## Notes

- OAH is standard unless specified.
- FINISH: PRIMARY FINISH = Canopy, support arms, corner extrusions, top and bottom plates. SECONDARY FINISH = Accent panels. Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Heavy gauge solid aluminum top and bottom frames with custom extruded aluminum corners. The side trim panels can be ordered with complementary color or finish.
- MOUNTING: Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

**HB-381** 8"W x 22"H x 8"L x 10" Ext. 30" Oah.  
**HB-382** 10"W x 30"H x 10"L x 13" Ext. 39" Oah.  
**HB-384** 12"W x 36"H x 12"L x 16" Ext. 46" Oah.

### 2 Finish

#### Primary Finish

Brushed Solid Aluminum (BA)  
 Standard Painted Finishes (PT)

#### Secondary Finish

Brushed Solid Aluminum (BA)  
 Standard Painted Finishes (PT)

### 3 Lamping

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### HB-381

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P63 Body (27w) + Downlight (36w)	5471 (delivered)	63

#### Non-LED Lamps

1N150: (1) 150 watt incandescent

#### HB-382

LED Options	Lumens	Wattage
P40 Body only w/bottom lens (40w)	3796 (delivered)	40
P88 Body (40w) + Downlight (48w)	8128 (delivered)	88
U18 Optional Uplight (18w)	1613 (delivered)	18

#### Non-LED Lamps

8N60 / 1QP250: (8) 60 watt incandescent & (1) 250 watt PAR38 med. base

#### HB-384

LED Options	Lumens	Wattage
P54 Body only w/bottom lens (54w)	5555 (delivered)	54
P109 Body (54w) + Downlight (55w)	11760 (delivered)	109
P150 Body (54w) + Downlight (96w)	14818 (delivered)	150
U44 Optional Uplight (44w)	4038 (delivered)	44

#### Non-LED Lamps

10N60 / 1QP250: (10) 60 watt incandescent & (1) 250 watt PAR38 med. base

### 4 LED Color Temp

27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

### 5 LED Dimming

D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

### 6 Downlight Optics Options

ECR: Black Egg Crate Louver (approx. 40-deg. beam)  
 BGL: Baffle & glass lens (for QT & MHT lamps only)  
 LED: Reflector & bottom cover plate (for LED lamp options only)

### 7 Voltage Options

120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

### 8 Diffuser Options

WH: White Acrylic  
 CD: Ambia configured diffuser (specify option)

1

Fixture #

2

Primary Finish  
(Finish)

2

Secondary Fini  
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Downlight Opti

7

Voltage

8

Diffuser