



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Spun aluminum or brass backplate, machined font, and laser-cut support arms.
- MOUNTING: Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- White bottom acrylic lens standard.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**
DS-203 10.5"W x 15.75"H x 4" Ext.
- 2 Finish**
Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)
Polished Brass (PB)

- 3 Lamping**
LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LED Options	Lumens	Wattage
S12		12

- 4 LED Color Temp**
27: 2700K
30: 3000K
35: 3500K
40: 4000K
- 5 LED Dimming**
D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

- 6 Voltage Options**
120: 120 volt

- 7 Diffuser Options**
WH: Opal White Acrylic
CD: Ambia configured diffuser (specify option)

