



Notes

- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.
- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Solid aluminum canopy plate, extruded aluminum side rail, and machined accents can be ordered with either a painted or brushed aluminum finish.
- MOUNTING: Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- White bottom acrylic lens standard.
- ETL listed to UL standards for dry and damp locations

- 1 Fixture Number**
LP-370 6"W x 10"H x 10"L 36" Oah.
LP-372 6"W x 24"H x 10"L 50" Oah.

- 2 Finish**
 Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)

- 3 Lamping**
 LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LP-370

LED Options	Lumens	Wattage
P8	860 (initial)	8

- Non-LED Lamps**
 1N60: (1) 60 watt incandescent

LP-372

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P63 Body (27w) + Downlight (36w)	5471 (delivered)	63

- Non-LED Lamps**
 3NT40: (3) 40 watt T-10 incandescent

- 4 LED Color Temp**
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

- 5 LED Dimming**
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

- 6 Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**
 WH: Opal White Acrylic
 CD: Ambia configured diffuser (specify option)

