



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Solid machined aluminum support arms can be ordered with either a painted or brushed aluminum finish, white backplate standard.
- **MOUNTING:** Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- White bottom acrylic lens standard.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

## 1 Fixture Number

**LB-370** 9.5"W x 10"H x 4" Ext.

**LB-372** 9.5"W x 16"H x 4" Ext.

**LB-374** 9.5"W x 24"H x 4" Ext.

## 2 Finish

Brushed Solid Aluminum (BA)

Standard Painted Finishes (PT)

## 3 Lamping

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

### LB-370

LED Options	Lumens	Wattage
S7	612 (delivered)	7

### Non-LED Lamps

1NT40: (1) 40 watt T-10 incandescent

### LB-372

LED Options	Lumens	Wattage
S7	612 (delivered)	7

### Non-LED Lamps

2NT40: (2) 40 watt T-10 incandescent

### LB-374

LED Options	Lumens	Wattage
S16	995 (delivered)	16

### Non-LED Lamps

3NT40: (3) 40 watt T-10 incandescent

## 4 LED Color Temp

27: 2700K

30: 3000K

35: 3500K

40: 4000K

## 5 LED Dimming

D0: 0-10v

D1: Triac (Leading Edge)\*

D2: ELV (Trailing Edge)

## 6 Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

## 7 Diffuser Options

WH: White Acrylic

CD: Ambia configured diffuser (specify option)

1	2	3	4	5	6	7
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser