



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Solid machined aluminum support arms can be ordered with either a painted or brushed aluminum finish, white backplate standard.
- MOUNTING: Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- White bottom acrylic lens standard.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**
LB-370 9.5"W x 10"H x 4" Ext.
LB-372 9.5"W x 16"H x 4" Ext.
LB-374 9.5"W x 24"H x 4" Ext.

- 2 Finish**
 Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)

- 3 Lamping**
 LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LED Options

LED Options	Lumens	Wattage
S7	612 (delivered)	7

- Non-LED Lamps**
 1NT40: (1) 40 watt T-10 incandescent

LED Options

LED Options	Lumens	Wattage
S7	612 (delivered)	7

- Non-LED Lamps**
 2NT40: (2) 40 watt T-10 incandescent

LED Options

LED Options	Lumens	Wattage
S16	995 (delivered)	16

- Non-LED Lamps**
 3NT40: (3) 40 watt T-10 incandescent

- 4 LED Color Temp**
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

- 5 LED Dimming**
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

- 6 Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**
 WH: Opal White Acrylic
 CD: Ambia configured diffuser (specify option)

1	2	3	4	5	6	7
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser