



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- OAH is standard unless specified.
- HOUSING: White 1/8" thick extruded acrylic cylinder with heavy gauge aluminum end caps and machined aluminum 1/4" x 1/2" bar details.
- MOUNTING: Fixture supplied with canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
LP-554: Fixture requires structural support such as 2x4 blocking or 3/8" IP stud extending below finished ceiling.
- CIRCUITS: Dual circuiting for interior lamps and downlight standard.
- ETL listed to UL standards for dry and damp locations.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

- LP-550 50.25"H x 10.25" Dia. 76" Oah.
- LP-552 62.25"H x 10.25" Dia. 88" Oah.
- LP-554 109.25"H x 10.25" Dia. 135" Oah.

2 Finish

- Housing, Stem & Canopy**
- Standard Painted Finishes (PT)
- Brushed Solid Aluminum (BA)

3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LP-550

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P57 Body Only (57w)	6042 (delivered)	57
P80 Body (57w) + Downlight (23w)	8210 (delivered)	80

Non-LED Lamps

- 3FX25T8: (3) 25 watt T8 bipin fluorescent lamps
- 3FX25T8 / 1QP250: (3) 25 watt T8 bipin fluorescent lamps & (1) 250 watt PAR38 med. base

LP-552

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P115 Body Only (115w)	12088 (delivered)	115
P138 Body (115w) + Downlight (23w)	14256 (delivered)	138

Non-LED Lamps

- 3FX32T8: (3) 32 watt T8 bipin fluorescent lamps
- 3FX32T8 / 1QP250: (3) 32 watt T8 bipin fluorescent lamps & (1) 250 watt PAR38 med. base

LP-554

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P230 Body Only (230w)	24177 (delivered)	230
P253 Body (230w) + Downlight (23w)	26345 (delivered)	253

Non-LED Lamps

- 3FX59T8: (3) Osram Sylvania Octron 800 XP Ecologic 32 watt T8 single pin fluorescent lamps
- 3FX59T8 / 1QP250: (3) Osram Sylvania Octron 800 XP Ecologic 32 watt T8 single pin fluorescent lamps & (1) 250 watt PAR38 med. base

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)*
- D2: ELV (Trailing Edge)

6 Downlight Optics Options

- B50: 50-deg. beam reflector

7 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

- WH: Opal White Acrylic

9 Fixture Options

- EMI: Integral Emergency Battery (Fluor.)
- DM (3FX25T8): Dimming for 3 x F25T8 Octron XPS compact fluorescent lamps

1

2

3

4

5

6

7

8

9

Fixture #

Housing, Stem
(Finish)

Lamping

Color Temp

Dimming

Downlight Opti

Voltage

Diffuser

Fixture Option