



## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- OAH is standard unless specified.
- HOUSING: Extruded aluminum corner bars with heavy gauge aluminum top and bottom panels and machined aluminum 1/4" x 1/2" bar details.
- MOUNTING: Fixture supplied with canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.  
LP-559: Fixture requires structural support such as 2x4 blocking or 3/8" IP stud extending below finished ceiling.
- CIRCUITS: Dual-level circuiting for interior lamps and downlight (if specified) standard.
- UL & ULc listed for dry and damp locations.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

- LP-555 10.25"W x 50.25"H x 10.25"L 76" Oah.
- LP-557 10.25"W x 62.25"H x 10.25"L 88" Oah.
- LP-559 10.25"W x 109.25"H x 10.25"L 135" Oah.

### 2 Finish

- Housing, Stem & Canopy**
- Standard Painted Finishes (PT)

### 3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency. Two-circuit wiring standard.

#### LP-555

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P57 Body Only (57w)	5166 (delivered)	57
P80 Body (57w) + Downlight (23w)	7334 (delivered)	80

#### Non-LED Lamps

- 3FX25T8: (3) 25 watt T8 bipin fluorescent lamps
- 3FX25T8 / 1QP250: (3) 25 watt T8 bipin fluorescent lamps & (1) 250 watt PAR38 med. base

#### LP-557

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P115 Body Only (115w)	10332 (delivered)	115
P138 Body (115w) + Downlight (23w)	12500 (delivered)	138

#### Non-LED Lamps

- 3FX32T8: (3) 32 watt T8 bipin fluorescent lamps
- 3FX32T8 / 1QP250: (3) 32 watt T8 bipin fluorescent lamps & (1) 250 watt PAR38 med. base

#### LP-559

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P230 Body Only (230w)	20664 (delivered)	230
P253 Body (230w) + Downlight (23w)	22832 (delivered)	253

#### Non-LED Lamps

- 3FX59T8: (3) Osram Sylvania Octron 800 XP Ecologic 32 watt T8 single pin fluorescent lamps
- 3FX59T8 / 1QP250: (3) Osram Sylvania Octron 800 XP Ecologic 32 watt T8 single pin fluorescent lamps & (1) 250 watt PAR38 med. base

### 4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

### 5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)

### 6 Downlight Optics Options

- B50: COB array with 50-deg. beam reflector

### 7 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

### 8 Diffuser Options

- WH: Opal White Acrylic

### 9 Fixture Options

- FU: Fusing
- EMI: Integral Emergency Battery (Fluor.)
- DM (3FX25T8): Dimming for 3 x F25T8 Octron XPS compact fluorescent lamps

1

2

3

4

5

6

7

8

9

Fixture #

Housing, Stem  
(Finish)

Lamping

Color Temp

Dimming

Downlight Opti

Voltage

Diffuser

Fixture Option