



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Machined aluminum tube with spun aluminum mounting plate.
- MOUNTING: Fixture mounts to standard octagonal electrical box. LB-552: Mounting plate has auxiliary mounting holes for attachment to structural blocking to support fixture (required).
- ETL listed to UL standards for dry and damp locations.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

LB-550 2.75"W x 31"H x 3.75" Ext.
LB-552 4"W x 44"H x 6.75" Ext.

2 Finish

Housing
 Standard Painted Finishes (PT)
 Brushed Solid Aluminum (BA)

3 Lamping

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LB-550

LED Options	Lumens	Wattage
S9	1308 (initial)	9

LB-552

LED Options	Lumens	Wattage
S23	2307 (initial)	23

4 LED Color Temp

27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: Opal White Acrylic

1

Fixture #

2

Housing
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser