


**1 Fixture Number**

LP-555	10.25"W x 50.25"H x 10.25)L 76" Oah.
LP-557	10.25"W x 62.25"H x 10.25)L 88" Oah.
LP-559	10.25"W x 109.25"H x 10.25)L 135" Oah.

**2 Finish**
**Housing, Stem & Canopy**

Standard Painted Finishes (PT)

**3 Lamping**

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**LP-555**

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P57 Body Only (57w)	6042 (delivered)	57
P80 Body (57w) + Downlight (23w)	8210 (delivered)	80

**LP-557**

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P115 Body Only (115w)	12088 (delivered)	115
P138 Body (115w) + Downlight (23w)	14256 (delivered)	138

**LP-559**

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P230 Body Only (230w)	24177 (delivered)	230
P253 Body (230w) + Downlight (23w)	26345 (delivered)	253

**4 LED Color Temp**

27: 2700K

30: 3000K

35: 3500K

40: 4000K

**5 LED Dimming**

D0: 0-10v

D1: Triac (Leading Edge)\*

D2: ELV (Trailing Edge)

**6 Downlight Optics Options**

B50: 50-deg. beam reflector

**7 Voltage Options**

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

**8 Diffuser Options**

WH: White Acrylic

<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>	<b>6</b>	<b>7</b>	<b>8</b>
Fixture #	Housing, Stem (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser