



## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- OAH is standard unless specified.
- HOUSING: Extruded aluminum corner bars with heavy gauge aluminum top and bottom panels and machined aluminum 1/4" x 1/2" bar details.
- MOUNTING: Fixture supplied with canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.  
LP-559: Fixture requires structural support such as 2x4 blocking or 3/8" IP stud extending below finished ceiling.
- CIRCUITS: Dual-level circuiting for interior lamps and downlight (if specified) standard.
- ETL listed to UL standards for dry and damp locations.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**
  - LP-555** 10.25"W x 50.25"H x 10.25"L 76" Oah.
  - LP-557** 10.25"W x 62.25"H x 10.25"L 88" Oah.
  - LP-559** 10.25"W x 109.25"H x 10.25"L 135" Oah.

- 2 Finish**
  - Housing, Stem & Canopy**
  - Standard Painted Finishes (PT)

- 3 Lamping**
  - LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.
  - LP-555**
  - LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P57 Body Only (57w)	6042 (delivered)	57
P80 Body (57w) + Downlight (23w)	8210 (delivered)	80

- LP-557**
- LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P115 Body Only (115w)	12088 (delivered)	115
P138 Body (115w) + Downlight (23w)	14256 (delivered)	138

- LP-559**
- LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P230 Body Only (230w)	24177 (delivered)	230
P253 Body (230w) + Downlight (23w)	26345 (delivered)	253

- 4 LED Color Temp**
  - 27: 2700K
  - 30: 3000K
  - 35: 3500K
  - 40: 4000K
- 5 LED Dimming**
  - D0: 0-10v
  - D1: Triac (Leading Edge)\*
  - D2: ELV (Trailing Edge)

- 6 Downlight Optics Options**
  - B50: 50-deg. beam reflector

- 7 Voltage Options**
  - 120: 120 volt
  - 277: 277 volt (Not available with incandescent lamp options)

- 8 Diffuser Options**
  - WH: Opal White Acrylic

