



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **OAH** is standard unless specified.
- **HOUSING:** Extruded aluminum corner bars with heavy gauge aluminum top and bottom panels and machined aluminum 1/4" x 1/2" bar details.
- **MOUNTING:** Fixture supplied with canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.  
LP-559: Fixture requires structural support such as 2x4 blocking or 3/8" IP stud extending below finished ceiling.
- **CIRCUITS:** Dual-level circuiting for interior lamps and downlight (if specified) standard.
- ETL listed to UL standards for dry and damp locations.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

|               |  |
|---------------|--|
| <b>LP-555</b> | 10.25"W x 50.25"H x 10.25"L 76" Oah.   |
| <b>LP-557</b> | 10.25"W x 62.25"H x 10.25"L 88" Oah.   |
| <b>LP-559</b> | 10.25"W x 109.25"H x 10.25"L 135" Oah. |

### 2 Finish

**Housing, Stem & Canopy**  
Standard Painted Finishes (PT)

### 3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### LP-555

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

| LED Options                      | Lumens           | Wattage |
|----------------------------------|------------------|---------|
| P57 Body Only (57w)              | 6042 (delivered) | 57      |
| P80 Body (57w) + Downlight (23w) | 8210 (delivered) | 80      |

#### LP-557

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

| LED Options                        | Lumens            | Wattage |
|------------------------------------|-------------------|---------|
| P115 Body Only (115w)              | 12088 (delivered) | 115     |
| P138 Body (115w) + Downlight (23w) | 14256 (delivered) | 138     |

#### LP-559

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

| LED Options                        | Lumens            | Wattage |
|------------------------------------|-------------------|---------|
| P230 Body Only (230w)              | 24177 (delivered) | 230     |
| P253 Body (230w) + Downlight (23w) | 26345 (delivered) | 253     |

### 4 LED Color Temp

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

### 5 LED Dimming

D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

### 6 Downlight Optics Options

B50: 50-deg. beam reflector

### 7 Voltage Options

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

### 8 Diffuser Options

WH: White Acrylic

|           |                           |         |            |         |                |         |          |
|-----------|---------------------------|---------|------------|---------|----------------|---------|----------|
| 1         | 2                         | 3       | 4          | 5       | 6              | 7       | 8        |
| Fixture # | Housing, Stem<br>(Finish) | Lamping | Color Temp | Dimming | Downlight Opti | Voltage | Diffuser |