



## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Extruded aluminum corner bars with fabricated aluminum end caps.
- MOUNTING: Fixture mounts to a standard rectangular (handy) box 2-1/8x4. Auxiliary fasteners required. LB-557: Mounting plate has auxiliary mounting holes for attachment to structural blocking to support fixture (required).
- ETL listed to UL standards for dry and damp locations.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**  
**LB-555** 4"W x 30"H x 4" Ext.  
**LB-557** 4"W x 44"H x 6.75" Ext.

- 2 Finish**  
**Housing**  
 Standard Painted Finishes (PT)

- 3 Lamping**  
 LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**LB-555**

LED Options	Lumens	Wattage
S16	995 (delivered)	16

**LB-557**

LED Options	Lumens	Wattage
S24	2580 (initial)	24

- 4 LED Color Temp**  
 27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K
- 5 LED Dimming**  
 D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

- 6 Voltage Options**  
 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**  
 WH: Opal White Acrylic  
 FX: Faux Alabaster Acrylic

