
Kiosk Square Sconce





Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Extruded aluminum corner bars with fabricated aluminum end caps.
- MOUNTING: Fixture mounts to a standard rectangular (handy) box 2-1/8x4. Auxiliary fasteners required. LB-557: Mounting plate has auxiliary mounting holes for attachment to structural blocking to support fixture (required).
- ETL listed to UL standards for dry and damp locations.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

LB-555 4"W x 30"H x 4" Ext.

LB-557 4"W x 44"H x 6.75" Ext.

2 Finish

Housing

Standard Painted Finishes (PT)

3 Lamping

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LB-555

LED Options	Lumens	Wattage
S16	995 (delivered)	16

LB-557

LED Options	Lumens	Wattage
S24	2580 (initial)	24

4 LED Color Temp

27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming

D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic
FX: Faux Alabaster Acrylic

1	2	3	4	5	6	7
Fixture #	Housing (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser

©2018 Manning Lighting Inc. Sheboygan, WI 53083 Phone: 920-458-2184 Web: manningltg.com Email: info@manningltg.com Design modification rights reserved. Made in USA.