

Lakefront Exterior Sconce





DE-720



DE-722

1 Fixture Number

DE-720 11.5"W x 22.3"H x 6.25" Ext.

DE-722 11.5"W x 36"H x 6.25" Ext.

2 Finish

End Caps/Frame
Standard Painted Finishes (PT)

Bars & Rods
Standard Painted Finishes (PT)

3 Lamping

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DE-720

LED Options	Lumens	Wattage
E17	1226 (initial)	17

Non-LED Lamps
2N60: (2) 60 watt incandescent

DE-722

LED Options	Lumens	Wattage
E23	1636 (initial)	23

Non-LED Lamps
3N60: (3) 60 watt incandescent

4 LED Color Temp
27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming
D0: 0-10v

6 Voltage Options
120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options
WH: White Acrylic
FX: Faux Alabaster Acrylic

8 Fixture Options
PC: Photo Cell

Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of solid machined aluminum bar details, extruded aluminum corner posts and solid cast aluminum end caps.
- MOUNTING: Fixture supplied with gasketed universal mounting plate for installation over standard octagonal junction box.
- ETL listed to UL standards for wet locations.

1	2	2	3	4	5	6	7	8
Fixture #	End Caps/Frame (Finish)	Bars & Rods (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Fixture Option

©2018 Manning Lighting Inc. Sheboygan, WI 53083 Phone: 920-458-2184 Web: manningltg.com Email: info@manningltg.com Design modification rights reserved. Made in USA.