



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Heavy gauge solid aluminum fabricated housing, extruded support arms, and machined aluminum diffuser clamps can be ordered with complementary finishes.
- MOUNTING: Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- UL and C-UL listed for dry or damp locations.

1 Fixture Number

LB-360 10.5"W x 10"H x 4" Ext.

LB-362 24"W x 6.75"H x 4" Ext.

LB-364 48"W x 6.75"H x 4" Ext.

2 Finish

Brushed Solid Aluminum (BA)

Standard Painted Finishes (PT)

3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LB-360

LED Options	Lumens	Wattage
S7	612 (delivered)	7

Non-LED Lamps

1NT40: (1) 40 watt T-10 incandescent

2F13: (2) 13 watt compact fluorescent

LB-362

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps

3NT40: (3) 40 watt T-10 incandescent

1F40: (1) 40 watt compact fluorescent

LB-364

LED Options	Lumens	Wattage
S30	3440 (initial)	30

Non-LED Lamps

2F40: (2) 40 watt compact fluorescent

4 LED Color Temp

27: 2700K

30: 3000K

35: 3500K

40: 4000K

5 LED Dimming

D0: 0-10v

D1: Triac (Leading Edge)*

D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: Opal White Acrylic

CD: Ambia configured diffuser

8 Fixture Options

EMW: Recessed Wall Emergency Battery (Fluor.)

FU: Fusing

*SP: 10kA surge protector (Recommended for D1 dimming option)

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Fixture Option