



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- OAH is standard unless specified.
- HOUSING: Extruded aluminum corner supports, machined accents, steel stem, and fabricated steel square canopy can be ordered with complementary finishes. Internal frame components in highly reflective white enameled aluminum.
- MOUNTING: Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- CIRCUITS: Dual-level circuiting for interior lamps/downlight standard.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**
LP-360 10"W x 10"H x 10"L 35" Oah.
LP-362 10"W x 24"H x 10"L 49" Oah.

- 2 Finish**
 Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)

- 3 Lamping**
 LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LP-360

LED Options	Lumens	Wattage
P16	2200 (initial)	16

- Non-LED Lamps**
 1N75: (1) 75 watt incandescent

LP-362

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P63 Body (27w) + Downlight (36w)	5471 (delivered)	63

- Non-LED Lamps**
 1N150: (1) 150 watt incandescent

- 4 LED Color Temp**
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K
- 5 LED Dimming**
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

- 6 Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**
 WH: Opal White Acrylic
 CD: Ambia configured diffuser (specify option)

1	2	3	4	5	6	7
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser