



## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Heavy gauge solid aluminum fabricated housing, extruded support arms, and machined aluminum diffuser clamps can be ordered with complementary finishes.
- MOUNTING: Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

- LB-360** 10.5"W x 10"H x 4" Ext.
- LB-362** 24"W x 6.75"H x 4" Ext.
- LB-364** 48"W x 6.75"H x 4" Ext.

### 2 Finish

- Brushed Solid Aluminum (BA)
- Standard Painted Finishes (PT)

### 3 Lamping

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### LB-360

LED Options	Lumens	Wattage
S7	612 (delivered)	7

#### Non-LED Lamps

1NT40: (1) 40 watt T-10 incandescent

#### LB-362

LED Options	Lumens	Wattage
S16	995 (delivered)	16

#### Non-LED Lamps

3NT40: (3) 40 watt T-10 incandescent

#### LB-364

LED Options	Lumens	Wattage
S30	3440 (initial)	30

### 4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

### 5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)

### 6 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

### 7 Diffuser Options

- WH: Opal White Acrylic
- CD: Ambia configured diffuser (specify option)

1

Fixture #

2

Finish  
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser