



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Heavy gauge solid aluminum fabricated housing, extruded support arms, and machined aluminum diffuser clamps can be ordered with complementary finishes.
- **MOUNTING:** Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

LB-360	10.5"W x 10"H x 4" Ext.
LB-362	24"W x 6.75"H x 4" Ext.
LB-364	48"W x 6.75"H x 4" Ext.

2 Finish

Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)

3 Lamping

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LB-360

LED Options	Lumens	Wattage
S7	612 (delivered)	7

Non-LED Lamps

1NT40: (1) 40 watt T-10 incandescent

LB-362

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps

3NT40: (3) 40 watt T-10 incandescent

LB-364

LED Options	Lumens	Wattage
S30	3440 (initial)	30

4 LED Color Temp

27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming

D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic
CD: Ambia configured diffuser (specify option)

1	2	3	4	5	6	7
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser