









# Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Heavy gauge solid aluminum fabricated housing, extruded support arms, and machined aluminum diffuser clamps can be ordered with complementary finishes.
- MOUNTING: Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

#### **Fixture Number**

LB-360 10.5"W x 10"H x 4" Ext. LB-362 24"W x 6.75"H x 4" Ext. LB-364 48"W x 6.75"H x 4" Ext.

Finish

Brushed Solid Aluminum (BA)

Standard Painted Finishes (PT)

### Lamping

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

### LB-360

| LED Options | Lumens          | Wattage |
|-------------|-----------------|---------|
| S7          | 612 (delivered) | 7       |

## Non-LED Lamps

1NT40: (1) 40 watt T-10 incandescent

### LB-362

| LED Options | Lumens          | Wattage |
|-------------|-----------------|---------|
| S16         | 995 (delivered) | 16      |

### Non-LED Lamps

3NT40: (3) 40 watt T-10 incandescent

### LB-364

| LED Options | Lumens         | Wattage |
|-------------|----------------|---------|
| S30         | 3440 (initial) | 30      |

**LED Dimming** 

**LED Color Temp** 27: 2700K

D0: 0-10v 30: 3000K D1: Triac (Leading Edge)\* 35: 3500K D2: ELV (Trailing Edge) 40: 4000K

**Voltage Options** 

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

# **Diffuser Options**

WH: Opal White Acrylic

CD: Ambia configured diffuser (specify option)