

Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Solid spun aluminum cylinder with white acrylic diffuser panels behind perforated design (if selected).
- MOUNTING: Fixture supplied with painted canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- CIRCUITS: Dual-level circuiting for interior lamps/downlight standard.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

- LP-196** 22"H x 8" Dia. 48" Oah.
LP-197 30"H x 10" Dia. 68" Oah.
LP-198 36"H x 12" Dia. 86" Oah.

2 Finish

Housing & Trim

- Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)

3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LP-196

| LED Options | Lumens | Wattage |
|----------------------------------|----------------|---------|
| P50 Body (14w) + Downlight (36w) | 5881 (initial) | 50 |

Non-LED Lamps

1N200: 200 watt A-21 med. base

LP-197

| LED Options | Lumens | Wattage |
|----------------------------------|------------------|---------|
| P62 Body (14w) + Downlight (48w) | 6920 (initial) | 62 |
| U18 Optional Uplight (18w) | 1613 (delivered) | 18 |

Non-LED Lamps

2N100 / 1R300: (2) 100 watt incandescent & (1) 300 watt R40 med. base

LP-198

| LED Options | Lumens | Wattage |
|----------------------------------|------------------|---------|
| P70 Body (14w) + Downlight (55w) | 8600 initial | 70 |
| U44 Optional Uplight (44w) | 4038 (delivered) | 44 |

Non-LED Lamps

2N100 / 1R500: (2) 100 watt incandescent & (1) 500 watt R40 med. base

4 LED Color Temp

- 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

- D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)


6 Downlight Optics Options

- B60: 60-deg. beam reflector
 B90: 90-deg. beam reflector
 CON: Concentric Ring Louver (approx. 50-deg. beam)

7 Voltage Options

- 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

8 Panel Options



| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|-----------|-------------------------|---------|------------|---------|----------------|---------|-------|
| Fixture # | Housing & Trim (Finish) | Lamping | Color Temp | Dimming | Downlight Opti | Voltage | Panel |